

PRESTO W85 Process System

High cooling capacities enable extremely low temperatures down to -85 °C possible. The high heating capacity, particularly with the A85t and the W85t, provides even more flexibility in the application.

Your advantages

- For highly precise, external temperature applications
- Rapid heating and cooling
- Wide working temperature ranges without changing fluids
- Highest performance with small footprint
- Space-saving design optimizes space utilization in your lab
- 5,7" industrial color TFT touch screen
- USB connection
- Ethernet
- SD-Card slot
- RS232
- Modbus
- RS485 (Accessory)
- Profibus DP (Accessory)
- CCC Anschlüsse für Alarm-Ausgang, Pt100-Externfühler und Standby-Eingang
- Removable ventilation grid
- Pump pressure up to 3.2 bar, max. flow rate 80 l/min
- Heating capacity up to 15 kW
- Cooling capacity up to 2.8 kW



Technical data

Available voltage versions		Cooling	
Order No.	9 421 852	Cooling of compressor	2-stage Water
Available voltage versions:		Cooling water pressure max. bar	6 ... 5.5
9 421 852.07	400V/3PNPE/50Hz (Plug 32A CEE)	Cooling water difference pressure bar	0.5
9 421 852.16	208-230V/3PPE/60Hz (Without Plug)	Cooling water consumption l/min	2 ... 6
9 421 852.06	230V/3PPE/50Hz (Plug 63A CEE)		
Other		Electronics	
Sound pressure level dba	69	External pt100 sensor connection	integrated
Classification	Classification III (FL)	2nd external Pt100 sensor connection	accessory
IP Code	IP 21	Integrated programmer	8x60 steps
Pump type	Centrifugal Pump	Temperature control	ICC
Pump type Magnetically coupled	1	Absolute temperature calibration	3 Point Calibration
		Temperature display	5.7" TFT Touchscreen
		Temperature setting	Touchscreen
Dimensions and volumes		Temperature values	
Filling volume expansion vessel l	11	Setting display resolution °C	0.01
Internal usable expansion volume l	7	Working temperature range °C	-85.0 ... +250.0
Minimal process volume l	9.5	Temperature stability °C	+/-0.05 ... +/-0.1
Active heat exchanger volume l	5	Ambient temperature °C	+5.0 ... +40.0
Weight kg	335	Temperature display resolution °C	0.01
Cooling Water Connection in	G $\frac{3}{4}$		
Dimensions cm (W x L x H)	61 x 84.5 x 125		
Pump connections	M30x1.5 male		

Power and capacities

400V/3PNPE/50Hz (Plug 32A CEE)

400V/3PNPE/50Hz								
Heating capacity kW					6			
Cooling capacity (Ethanol)								
°C	200	20	0	-20	-30	-40	-60	-80
kW	2.8	2.5	2.4	2.4	2.4	2.4	2.2	0.4
Viscosity max. cST					50			
Refrigerant					R507			
Filling volume g					1600			
Global Warming Potential for R507					3985			
Carbon dioxide equivalent t					6.376			
Refrigerant					R23			
Filling volume g					680			
Global Warming Potential for R23					14800			
Carbon dioxide equivalent t					10.064			
Pump capacity flow rate l/min					35 ... 80			
Pump capacity flow pressure bar					0.48 ... 3.2			

208-230V/3PPE/60Hz (Without Plug)

208V/3PPE/60Hz								
Heating capacity kW				5.5				
Cooling capacity (Ethanol)								
°C	200	20	0	-20	-30	-40	-60	-80
kW	2.8	2.5	2.4	2.4	2.4	2.4	2.2	0.4
Viscosity max. cST				50				
Refrigerant				R507				
Filling volume g				1600				
Global Warming Potential for R507				3985				
Carbon dioxide equivalent t				6.376				
Refrigerant				R23				
Filling volume g				680				
Global Warming Potential for R23				14800				
Carbon dioxide equivalent t				10.064				
Pump capacity flow rate l/min				35 ... 80				
Pump capacity flow pressure bar				0.48 ... 3				

230V/3PPE/60Hz								
Heating capacity kW				6				
Cooling capacity (Ethanol)								
°C	200	20	0	-20	-30	-40	-60	-80
kW	2.8	2.5	2.4	2.4	2.4	2.4	2.2	0.4
Viscosity max. cST				50				
Refrigerant				R507				
Filling volume g				1600				
Global Warming Potential for R507				3985				
Carbon dioxide equivalent t				6.376				
Refrigerant				R23				
Filling volume g				680				
Global Warming Potential for R23				14800				
Carbon dioxide equivalent t				10.064				
Pump capacity flow rate l/min				35 ... 80				
Pump capacity flow pressure bar				0.48 ... 3.2				

230V/3PPE/50Hz (Plug 63A CEE)

230V/50Hz								
Heating capacity kW					6			
Cooling capacity (Ethanol)								
°C	200	20	0	-20	-30	-40	-60	-80
kW	2.8	2.5	2.4	2.4	2.4	2.4	2.2	0.4
Viscosity max. cST					50			

Refrigerant	R507
Filling volume g	1600
Global Warming Potential for R507	3985
Carbon dioxide equivalent t	6.376
Refrigerant	R23
Filling volume g	680
Global Warming Potential for R23	14800
Carbon dioxide equivalent t	10.064
Pump capacity flow rate l/min	35 ... 80
Pump capacity flow pressure bar	0.48 ... 3.2

Benefits



Touch display. Perfect operation.

With the touch display, the user always has an overview of all values and functions. The intuitive and multilingual menu structure enables perfect control.



Convenience for several users

Administrator level for customizing instrument settings, user levels with limited permissions for fast and safe defined access, password protection, all levels adjustable



100 % Cooling capacity

'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures



Intelligent temperature control.

Intelligent cascade control - automatic and self-optimizing adaptation of the PID control parameters with external stability of ± 0.05 °C.



Full control

'Temperature Control Features', for individual optimization, access to all important control parameters, additional settings for band limit, limits, co-speedfactor etc.



Control from the external application

External Pt100 sensor connection for precise measurement and control directly in the external application




Highest measuring accuracy

'Absolute Temperature Calibration' for manual compensation of a temperature difference, 3-point calibration




Intelligent pump system

Reliable and consistent pump capacity, electronically adjustable pump stages or pressure value, automatic adjustment of pump capacity to viscosity



Many interfaces.

Straight-forward remote control, data management, and integration into process structures. USB, Ethernet, RS232, SD card, and alarm off are permanently integrated. Further interfaces available as accessories.



Space-saving footprint

All connections as well supply and exhaust air are located at the front or rear, no venting grids on the sides, units can be placed close to each other or the application



Continuous operation up to +40 °C

Robust temperature control instrument, continuous operation even at ambient temperatures of up to +40 °C



Maximum safety.

Classification III according to DIN12876-1 enables safe operation, even with flammable fluids. Automatic switch-off in the event of high temperature or low liquid level.



Duplicate safety

Adjustable high temperature cut-off for internal tank and for integrated expansion vessel



For flammable bath fluid

Classification III (FL) according to DIN 12876-1



Quick support

If an error occurs, the integrated Black-Box function permits fast diagnosis by the JULABO service team




JULABO. Quality.

Highest standards of quality for a long product life.



Green technology.

Development consistently applied environmentally friendly materials and technologies.



Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



100% Checked.

100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.



Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.